








TECHNICAL DATA



Aluminium Extrusion

Specification	Product	
Product code	CL-ALU-1-2M-S	CL-ALU-1-2M-R
		
Material	Anodised aluminium	Anodised aluminium
Use	Indoor only	Indoor only
Cover options	Clear or frosted	Clear or frosted
End caps	Supplied	Supplied
Fixing	Surface mounted. Screw through base or brackets supplied Push on cover	Recessed. Screw through base or brackets supplied Push on cover
Dimensions (mm)		
Outer width	15.2	22
Internal width	11.2	11.2
Depth	6	5.9
Length	2000	2000
Quality		
Grade	Commercial	Commercial
Warranty	2 years	2 years

Specification	Product	
Product code	CL-ALU-2-2M-S	CL-ALU-2-2M-R
		
Material	Anodised aluminium	Anodised aluminium
Use	Indoor only	Indoor only
Cover options	Clear or frosted	Clear or frosted
End caps	Supplied	Supplied
Fixing	Surface mounted. Screw through base or brackets supplied Push on cover	Recessed. Screw through base or brackets supplied Push on cover
Dimensions (mm)		
Outer width	16	22
Internal width	11.2	11.2
Depth	12	11.87
Length	2000	2000
Quality		
Grade	Commercial	Commercial
Warranty	2 years	2 years



Specification	Product	
Product code	CL-ALU-3-2M-S	CL-ALU-4-2M-C-90
		
Material	Anodised aluminium	Anodised aluminium
Use	Indoor only	Indoor only
Cover options	Clear or frosted	Clear or frosted
End caps	Supplied	Supplied
Fixing	Surface mounted. Screw through base or brackets supplied Push on cover	90° Corner fixing. Screw through base or brackets supplied Push on cover
Dimensions (mm)		
Outer width	23	16
Internal width	20.6	10
Depth	10	16
Length	2000	2000
Quality		
Grade	Commercial	Commercial
Warranty	2 years	2 years

Product code	CL-ALU-5-2M-O-30	CL-ALU-5-2M-O-60
		
Lens angle	30°	60°
Material	Anodised aluminium	Anodised aluminium
Use	Indoor only	Indoor only
Cover options	Clear or frosted	Clear or frosted
End caps	Supplied	Supplied
Fixing	Screw through base or brackets supplied Push on cover	Screw through base or brackets supplied Push on cover
Dimensions (mm)		
Outer width	17.6	17.5
Internal width	12	12.2
Depth (inc. lens)	12	13.4
Length	2000	2000
Quality		
Grade	Commercial	Commercial
Warranty	2 years	2 years